

Silverline 60 RGBW



The silverline 60 RGBW is a flexible LED that is capable of creating vibrant and vivid colours. The use of RGBW LED's allows the user to create any mood required and transforms the visual impact of a space.

It is equipped with 3M self-adhesive tape which allows itself for easy placement on almost any water and dust free surface.

Its flexible in its design, where each length is cut able in 50mm lengths.

A wide range of aluminium profiles and covers are available.

Features

Design flexibility Cutable every 50mm Easy installation Adhesive tape



Vivid colours RGBW led

Technical specifications

LED

Colour: Colour temperature: LED's per meter: Lumen output: RGBW 2700K / 4000K 60 98 lumen (R) 362 lumen (G) 90 lumen (B) 356 lumen (2700K) 383 lumen (4000K)

Power

Power: Consumption per meter: Maximum length: 24VDC 19,2W 5 meter on single ended power supply


Miscellaneous

Lifespan: IP rating: Length per reel: Cut length: Strip width: Beam angle: 20.000 hour IP20 5 meter ± 10mm 50mm ± 1mm 12mm ± 0,1mm 120°



Silverline 60 RGBW

Dimensions



Wiring

Use min 90°C supply conductors when connecting to the silverline 60 RGBW flexible LED strip.

A cable with 5 conducters is needed for the silverline 60 RGBW flexible LED strip

Only use power supplies which can deliver a constant dc-voltage between 21 $\sim\!24\text{VDC}.$

Order Code

FLX.S.RGBW27.60.0A FLX.S.RGBW40.60.0A Flex led silverline 60 LED/m; RGBW; 2700K White; 24VDC; 19,2W/M; 500cm Reel
Flex led silverline 60 LED/m; RGBW; 4000K White; 24VDC; 19,2W/M; 500cm Reel