

Silverline 60 tunable white



The silver line 60 tunable white is a flexible LED that allows mood control due to the dual colour temperature LED's. It is equipped with 3M self-adhesive tape which allows itself for easy placement on almost any water and dust free surface. The silver line 60 is very suitable for cove and signage applications.

Its flexible in its design, where each length is cut able in 66,66mm lengths.

A wide range of aluminium profiles and covers are available.

Features

Tunable White
2400~6000K

Easy installation
Adhesive tape

Design flexibility
Cutable every 66,66mm





Technical specifications

| | | |
|----------------------|------------------------|--|
| LED | Colour temperature: | 2400~6000K |
| | Colour rendering: | CRI > 80 |
| | LED's per meter: | 60 |
| | Lumen output: | 420 lumen (2400K) 480 lumen (6000K) |
| Power | Power: | 24VDC |
| | Consumption per meter: | 14,4W |
| | Maximum length: | 5 meter on single ended power supply |
| Miscellaneous | Lifespan: | 20.000 hour |
| | IP rating: | IP20 |
| | Length per reel: | 5 meter |
| | Cut length: | 66,66mm |
| | Strip width: | 10mm |
| | Beam angle: | 120° |

Silverline 60 tunable white

Dimensions



Wiring

Use min 90°C supply conductors when connecting to the silverline 60 tunable white flexible LED strip.

A cable with 3 conductors is needed for the silverline 60 tunable white flexible LED strip

Only use power supplies which can deliver a constant dc-voltage between 21 ~24VDC.

Order Code

FLX.S.TW.2465.60 - Silver Line TW 2400~6500K; 60LED/m; IP20; 15,6W/m; 24V; 5m