

Moodspot RGBW Downlight (Recessed)

Technical specifications

LED Colour: **RGBW**

> 5500K Colour temperature white: Colour rendering: 75

Colour variation: 3 MacAdam Elipse Lumen output: 1350 lumen (full RGBW) Dimming range: Smooth dimming to 0%

>90% Efficiency:

Power supply: 48VDC IZI-Link Power

> Current: 750mA Consumption: 40 Watt

Material: Aluminum (lens: PMMA) Miscellaneous

> Lifespan: > 50.000 hour Lenses: 13° / 20° / 35° / 45° Weight: 940 grams IP-Rating: IP20

300mm 2-core wire Cable length:

WAGO 770-252 / Winsta MIDI / 2-Connection:

Accessories Accessories: Honeycomb / Barndoors

> Connectors: WAGO male & female / T & H-block

Black or white finish Flange: Version

Driver: Built-in IZI-link driver Control

Control: IZI-link system

Dimensions


Overall dimensions: 148 x 134mm

135mm Cut out:

Housing: Adjustable (2x20°)









The Moodspot RGBW Downlight is a **RGBW LED spot** which alters the emotional experience of a certain space. Because of the RGBW LED technology the spot can create every thinkable colour, including white. With its internal IZI-link LED driver it can create vivid colours, the Moodspot is able to dim flicker free all the way down to 0%.

Features:

Smooth and flicker free dimming

RGBW - vivid colours

Extra White 5500K

Lifespan of 50.000+ hours

Warranty:

5 years


Certifications:






Photometric data


Polar chart 13° optic




Polar chart 20° optic



Polar chart 35° optic



Polar chart 45° optic



Order code

Lenses Lens 13° Lens 20° Lens 35° Lens 45°

Black finish MO.RGBW.R.B.13 MO.RGBW.R.B.20 MO.RGBW.R.B.35 MO.RGBW.R.B.45

White finish MO.RGBW.R.B.13 MO.RGBW.R.B.20 MO.RGBW.R.B.35 MO.RGBW.R.B.45

Accessories

Honeycomb Barndoors WAGO female WAGO male T-block + male & female MO2.CON2 connector


H-block + male & female connector

MO2.HC MO2.BD MO2.CON1 MO2.CON5

MO2.CON4



Minimum spacing





Luminaire not suitable for covering with thermal insulating materials. Allow air to flow freely around the fixture.

Connection IZI-Link

The following connection overview is a simplified overview of the system. For more detailed information about the IZI-Link system visit our website.

The Moodspot RGBW Downlight LED spot is prepared with a two wired cable.



Red: 48VDC IZI-Link (+)

Black: 0V (-)

